



Product Service

Attestation of Conformity

No. N8A 078488 0096 Rev. 04

Holder of Certificate: **Suzhou Talesun Solar Technologies Co., Ltd.**

No. 1 Talesun Road
Shajiabang, Changshu
215542 Suzhou, Jiangsu Province
PEOPLE'S REPUBLIC OF CHINA

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 704061707023-08

Date, 2020-09-24

(Zhulin Zhang)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 078488 0096 Rev. 04

Model(s):

1000 VDC system voltage normal modules:

- TP678M-xxx, xxx=400-415 in step of 5;
- TP672M-xxx, xxx=325-395 in step of 5;
- TP6H72M-xxx, xxx=365-415 in step of 5;
- TP6F72M-xxx, xxx=385-415 in step of 5;
- TP6G72M-xxx, xxx=390-420 in step of 5;
- TP6L72M-xxx, xxx=435-455 in step of 5;
- TP660M-xxx, xxx=270-330 in step of 5;
- TP6H60M-xxx, xxx=305-345 in step of 5;
- TP6F60M-xxx, xxx=320-345 in step of 5;
- TP6G60M- xxx, xxx=325-350 in step of 5;
- TP6L60M-xxx, xxx=360-380 in step of 5

1500 VDC system voltage normal modules:

- TP678M(H)-xxx, xxx=400-415 in step of 5;
 - TP672M(H)-xxx, xxx=325-395 in step of 5;
 - TP6H72M(H)-xxx, xxx=365-415 in step of 5;
 - TP6F72M(H)-xxx, xxx=385-415 in step of 5;
 - TP6G72M(H)-xxx, xxx=390-420 in step of 5;
 - TP6L72M(H)-xxx, xxx=435 to 455 in step of 5;
 - TP660M(H)-xxx, xxx=270-330 in step of 5;
 - TP6H60M(H)-xxx, xxx=305-345 in step of 5;
 - TP6F60M(H)-xxx, xxx=320-345 in step of 5;
 - TP6G60M(H)-xxx, xxx=325-350 in step of 5;
 - TP6L60M(H)-xxx, xxx=360-380 in step of 5,
- xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Safety Class:	Class II
Maximum System Voltage:	1000 V DC or 1500 V DC
Fire Safety Class:	Class C according to UL790
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute, No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China.

Tested according to:

- EN IEC 61730-1:2018
- EN IEC 61730-1:2018/AC:2018-06
- EN IEC 61730-2:2018
- EN IEC 61730-2:2018/AC:2018-06

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.