

eSolar AIO3



Multifunction in One
(Wi-Fi, Bluetooth, Ethernet)



OLED Screen



Bluetooth
Connection



Real-time
Data Reading

eSolar AIO3 Datasheet

General parameters	
Connecting inverters No. [set]	1
Inverter communication port	RS232 (USB joints)
Remote communication port	Wi-Fi / Ethernet
Data collection interval[min]	1~30 [Optional], 10 [standard]
Firmware update method	Serial port / Remote
Access data method	APP (Bluetooth connection) / Remote server
Status display	OLED
Electric parameters	
Input voltage [V]	DC 5~7 ($\pm 5\%$)
Static consumption [W]	<0.3
Max. instant consumption [W]	<4
Environment	
Operating temperature range	-40°C~+60°C
Storage temperature range	-45°C~+90°C
Dimensions [H*W*D][mm]	144*49*40
Weight [g]	84
Ingress protection	IP65
Others	
Mounting method	Plug-in+Screw lock
Warranty [Year]	2 [Standard] / 5 [Optional]

GUANGZHOU SANJING ELECTRIC CO., LTD.

Website: www.saj-electric.com

E-mail: info@saj-electric.com

Add:SAJ Innovation Park, No.9, Lizhishan Road, Science City, Guangzhou, Guangdong, P.R.China.

